

RECHARGEABLE

INTRANT™ DUAL-LIGHT ANGLE LIGHT

**NIGHTSTICK®**  
Life Depends on Light™



HEAD ROTATES 90°

45°


EXCLUSIVE  
DOWNWARD FLOODLIGHT



**Head rotates 90°** – directing beam exactly where it's needed most



**45° downward floodlight** lights an 8 foot walking area



**Easy-to-use with gloves**, the large switches **independently control** separate LEDs



**Heavy-duty, clip and V-ring** securely holds **tight to gear** in any situation

GRAB-N-GO  
CHARGING BASE



ALSO AVAILABLE IN SAFETY RED.



**205 LUMENS**

1-800-233-2155 • 1-469-326-9400 • [nightstick.com](http://nightstick.com)

# DUAL-LIGHT ANGLE LIGHT

## RECHARGEABLE

### ITEM NUMBER/UPC

XPR-5568RX (Red), 0 17398 80631 2  
 XPR-5568RXLB (Red, Light & Battery Only), 0 17398 80697 8  
 XPR-5568GX (Green), 0 17398 80630 5

### CERTIFICATIONS

- CE, cULus, ATEX, IECEx, InMetro, UKCA, KOSHA  
 - Meets requirements of NFPA

### PATENTS

- 9,713,217 10,119,663

### CASE MATERIAL

- Engineered polymer

### LUMENS/RUNTIME

#### FLASHLIGHT

- HIGH: 200L, 7 hrs. runtime  
 - MEDIUM: 110L, 15 hrs. runtime  
 - LOW: 60L, 27 hrs. runtime  
 - STROBE

#### FLOODLIGHT

- HIGH: 100L, 7 hrs. runtime  
 - MEDIUM: 40L, 15 hrs. runtime  
 - SURVIVAL: 20L, 27 hrs. runtime

#### DUAL-LIGHT

- 205L, 7 hrs. runtime

### CANDELA

#### FLASHLIGHT

- HIGH: 40,256  
 - MEDIUM: 15,625  
 - LOW: 8,750

### BEAM DISTANCE

#### FLASHLIGHT

- HIGH: 401m  
 - MEDIUM: 250m  
 - LOW: 187m

### WATER RATING

- IP-67 (dustproof and waterproof)

### DROP RATING

- 2 meters

### DIMENSIONS

- LENGTH: 6.6 in (168mm)  
 - WIDTH: 2.6 in (66mm)  
 - DEPTH: 2.6 in (66mm)  
 - HEAD DIAMETER: 2.1 in (53mm)  
 - WEIGHT: 10.6 oz (301g)(with batteries)

### BATTERY

- Rechargeable Li-ion battery pack  
 - AA Battery carrier (batteries not included)

### WARRANTY

- Limited lifetime warranty

### WHAT'S INCLUDED

- Angle light  
 - Rechargeable Li-ion battery pack  
 - AA battery carrier  
 - Snap-in rapid charger (Charge Input: 24VDC max) Meets requirements of NFPA  
 - AC & DC power supplies  
 - Instruction manual

FL 1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	200 LUMENS	60 LUMENS	205 LUMENS
	7h	27h	7h
	401m		
	40256cd		

**Bayco Product, Inc. XPR-5568**  
 640 S. Sanden Blvd., Wylie, TX 75098

Ex in FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS LISTED Ex in PARA USO EM LOCAS PERIGOSOS

For use with Bayco Lion Battery Pack 5568-BATT or 5568-CARRIER with 3 AA Energizer Type EN91 or E91 batteries only  
 Para uso com a bateria de íon de lítio Bayco 5568-BATT ou 5568-CARRIER com 3 baterias AA Energizer Tipo EN91 ou E91

E 457755  
 ID 400354

ELECTRICAL SAFETY  
 INTRINSICALLY SAFE  
 SECURITE INTRINSEQUE

CLASS I DIV 1 GRP A D T4 CLASS II & III DIV1 GRP E-G T130°C CLASS I ZONE 0 AEx ia IIC T4 Ga

© I 1 M1 Ex ia op in I Ma Ex ia op in I Ma  
 © I 1 G Ex ia op in IIC T4 Ga Ex ia op in IIC T4 Ga

US Patents 9,713,217 & 10,119,663

CE 2575 UK CA 0359  
 Meets the requirements of NFPA-1971-8.6 (2013)

DEMCO 11 ATEX 1527 UL2000C000 IECEx UL 17.0082 20°C ≤ Tamb ≤ +40°C 3.7VDCd Alkaline 3.7VDCd Li-ion IP-67 Um: 10V SEE INSTRUCTION MANUAL VORH MANUEL

Control Drawing: 5568-CERT-DWG1-03  
 For Battery Charger Connection see Instruction Manual Drawing: 5562-68-MECH-DWG1-09

MFG MM-YY

CERTIFIED									
CE	cULus LISTED	EX	IECEx	NFPA	UKCA 0359	INMETRO	BC	8	CS