



NEW HDL250 PRIME

- HDL250-23 PRIME 10.000.814
- HDL250-32 PRIME 10.000.816
- HDL250-42 PRIME 10.000.902

electronic water level indicator for optional 125 or 175 ltr built-on tank

pressure gauge

ignition on/off (red button)
start (green button)

battery loading

choke & accelerator

foam dosing 0 – 6 %



triplex (23 & 32 ltr) or vario (42 ltr) lance attachment

lifting eyes

hour counter & battery loading indicator

fork lift pockets



Technical Data	HDL250-23 PRIME	HDL250-32 PRIME	HDL 250-42 PRIME
dimensions(LxWxH mm)	1130x640x700	1130x640x700	1130x640x700
weight	170kg	170kg	170kg
drive (4-stroke-petrol-engine)	2-cyl. 13,2 kW	2-cyl. 13,2 kW	2-cyl. 13,2 kW
starter	electrically, recoil rope	electrically, recoil rope	electrically, recoil rope
pump	3-cyl. 23l/min.	3-cyl. 32l/min.	3-cyl. 42l/min.
pressure	250bar	200bar	130bar
high-pressure-hose	60m(500bar)	50m(500 bar)	50m(500 bar)
water tank (optional)	125 l / 175 l	125 l / 175 l	125 l / 175 l
foam suction	serial	serial	serial
spray attachment	TRIPLEX (23/32l), VARIO (42l)		