



**AFT 09/03**

## **BACKPACK AFT 09/03**

Advanced Firefighting Technology

- Water mist/CAFS extinguishing device
- Low Operating pressure
- Made in Germany
- Extremely powerful (A55/B233)
- Easy to use
- Stainless steel container made of V4A
- Suitable for many extinguishing agents
- Approved according to EN 3



## **ZIEGLER BACKPACK AFT 09/03**

Advanced Firefighting Technology



## BACKPACK AFT 09/03

EXTINGUISHING AGENT TANK	
Nominal volume according to EN 3	9 liter
Material	stainless steel
OPERATING PRESSURE	
Pressure reducer	8,5 bar
FUEL CYLINDER	
Medium	compressed air
Technical Characteristics	filling pressure 300 bar, Volume 2 litre, valve connection G5/8 inside
TECHNICAL PARAMETERS	
Working time	approx. 23 sec.
Flow rate	24 liter/min
Operating temperature	Tmin +5 °C, Tmax +60 °C
EXTINGUISHING PISTOL	
Change time	approx. 2 sec. from jet to spray
Distance	approx. 16-18 m (jet stream), approx. 6-7 m (spray jet)
Electrical system	up to 1.000 V at a distance of 3 m
RATINGS (EXTINGUISHING POWER E.G. WITH EXTINGUISHING AGENT ECODARE 423)	
Fire class A	55 A (according to EN 3)
Fire class B	233 B (according to EN 3), IIB (according to EN 1866)
MEASURES	
Empty weight (without compressed air bottle)	approx. 12,5 kg
Measures (L x W x H)	approx. 260 x 420 x 820 mm
CERTIFICATES	
Approvals	DIN EN 3, MED, GS, TÜV, ISO 9001 (producer)*

\* National and sectoral regulations must be considered as a priority.  
If you have any questions, please contact Albert Ziegler GmbH.



Albert Ziegler GmbH, Memminger Straße 28, 89537 Giengen/Brenz  
E-Mail [ziegler@ziegler.de](mailto:ziegler@ziegler.de), Phone +49 7322 951-0, Fax +497322 951-211,  
[www.ziegler.de](http://www.ziegler.de)