



AFT 12/01

BACKPACK AFT 12/01

Advanced Firefighting Technology

- Water mist/CAFS extinguishing device
- Low operating pressure
- Made in Germany
- Extremely powerful (A55/B233)
- Easy to use
- Stainless steel container made of V4A
- Suitable for many extinguishing agents
- Approval according to EN 3



ZIEGLER BACKPACK AFT 12/01

Advanced Firefighting Technology





BACKPACK AFT 12/01

EXTINGUISHING AGENT TANK	
Nominal volume	12 liter
Material	very light coal and aramid fiber
OPERATING PRESSURE	
Pressure at reducer	8,5 bar
FUEL CYLINDER	
Medium	compressed air
Technical Characteristics	filling pressure 300 bar, Volume 2 litre, valve connection G5/8 inside
TECHNICAL PARAMETERS	
Working time	approx. 30-32 seconds
Flow rate	24 liter/min
Operating temperature	Tmin +5 °C, Tmax +60 °C
EXTINGUISHING PISTOL	
Change time	approx. 2 sec. from jet to spray
Distance	approx. 16-18 m (jet stream), approx. 6-7 m (spray jet)
Elektrical system	up to 1.000 V at a distance of 3 m
RATINGS (EXTINGUISHING POWER E.G. WITH EXTINGUISHING AGENT ECODARE 423)	
Fire class A	55 A (according to EN 3)
Fire class B	233 B (according to EN 3), IIB (according to EN 1866)
MEASURES	
Empty weight (without compressed air bottle)	approx. 10 kg
Abmaße (L x W x H)	approx. 245 x 360 x 630 mm
CERTIFICATES	
Approvals	ISO 9001 (producer)*

* National and sectoral regulations must be considered as a priority.
If you have any questions, please contact Albert Ziegler GmbH.



Albert Ziegler GmbH, Memminger Straße 28, 89537 Giengen/Brenz
E-Mail ziegler@ziegler.de, Phone +49 7322 951-0, Fax +497322 951-211,
www.ziegler.de